

INSTALLATION GUIDE

**Mirror Monitor Replacement**

**NOTE:** The Voyager Mirror Monitor VOM74MM with Serial Number starting with an A, B, or C has been recalled due to the possibility of the image inverting. If a Field Fix Kit harness was installed. It should be removed if the monitor is replaced with a monitor that starts with E, F, or G. The Field Fix Kit harness is then not needed.



**Pre-installation check to verify power to Mirror Monitor (optional):**

1. Start vehicle. Monitor should turn ON. POWER LED should illuminate BLUE.
  - a. If monitor does not show image and POWER LED does not illuminate, check harness for +12V and check monitor vehicle circuit fuse.

**Locate the Monitor Connector.**

1. The Monitor Connector will most likely be pushed in the Headliner of the Vehicle.
2. The connector may be able to be carefully pulled out of the headliner or the headliner may need to be partially pulled down to access it. The Monitor Connector is 17" from the Monitor.



3. Once located, disconnect the Monitor Connector.

Original Release:	6/23/2020	Tracking Number:	IG10001CF
Current Revision:	A	Written By:	Alex peek
Revision Date:		Approved By:	Tim Welling
Description:	VOM74MM Mirror Monitor Replacement-THOR		

# INSTALLATION GUIDE

## Removing Monitor from Windshield.

1. To remove the Monitor from the Windshield mount, use a Phillips screwdriver to loosen the screw on the Mirror Mount stem.



2. Once loose, slide the monitor UP to remove it from the Windshield.

## Removing/Transferring Mirror Mount

1. Remove the Mirror Mount by removing the four screws that hold the Mount to the Monitor, shown below:



2. Install the Mirror Mount to the new Monitor using the same screws.

## Installing new Monitor

1. Slide Mirror Mount back onto Windshield.
2. Tighten the Phillips Head screw.
3. Reconnect the Monitor Connector and put Connector back into the Headliner.

## Post-installation check:

1. Start vehicle. Monitor should turn ON. POWER LED should illuminate BLUE.
  - a. If monitor does not show image and POWER LED does not illuminate, check harness for +12V and check monitor vehicle circuit fuse.
2. Put vehicle into REVERSE – monitor should activate and the rear view camera should activate. Put vehicle back into PARK.
3. Turn vehicle ignition OFF.

Original Release:	6/23/2020	Tracking Number:	IG10001CF
Current Revision:	A	Written By:	Alex peek
Revision Date:		Approved By:	Tim Welling
Description:	VOM74MM Mirror Monitor Replacement-THOR		