



DESIGNED TO MOVE [YOU][®]

Our Complete Line-up of Bluetooth[®] Stereos



JAH240BTR

- 80 watts (40 watt RMS)
- Bluetooth streaming audio (A2DP)
- Waterproof (IPX6)
- 4 Ohm ~ 8 Ohm stable
- Operating voltage: 10 - 18VDC
- Frequency response: 20Hz - 20KHz
- Flush mount lit power button
- Epoxy-potted enclosure
- 10 Amp fuse in waterproof holder
- UV resistant (ASTM D4329)
- Corrosion resistant (ASTM B117)

MS3ARTL

- 160 watts (40W x 4)
- Bluetooth interface capability (A2DP/AVRCP)
- Waterproof (IPX6)
- Rear USB input for MP3 enabled devices
- Rear AUX input (RCA)
- Line-out audio (RCA)
- Conformal coated circuit boards
- UV resistant (ASTM D4329)
- Corrosion resistant (ASTM B117)



MS2ARTL

- 160 watts (40W x 4)
- Waterproof (IPX5)
- Bluetooth interface capability (A2DP/AVRCP)
- iPod/iPhone ready via USB
- Rear AUX audio input (RCA)
- Pre-amp line out audio (RCA)
- Solid top chassis
- Conformal coated circuit boards
- UV resistant (ASTM D4329)
- Corrosion resistant (ASTM B117)

