

Voyager

**TOUGHGAM™**

1401582H1

# One-Camera Observation System



## 7" LCD Observation Monitor (AOM713)

- High-performance LCD panel
- Energy-efficient white LED backlighting
- Back-lit controls
- Integrated audio speaker
- NTSC and PAL video signal compatible
- Three camera (A/V) inputs
- Manual (push button) or automatic (trigger) source selection
- Auto power On (standby)
- Auto/manual day/night brightness modes
- On screen display (OSD) for AV source, picture adjustment and volume level
- OSD programmable source name and distance markers
- Non-volatile memory for picture and volume
- Anti-glare/anti-scratch protective lens
- Removable sun-visor included
- Multiple mounting options

## High-Performance Compact Color CMOS Cameras (VCMS50i)

- 12 volt power system
- High-performance color optics (Super CMOS)
- Waterproof (IP69K)
- NTSC video output signal format
- Sensitivity: 0 Lux (with IR LED ON)
- Viewing Angle: 150°, 120°, 90°
- IR LED for enhanced low-light performance
- FCC, E9 certified
- Corrosion resistant (ASTM B117)
- Dimensions: 1.5"W x 1.32"H x 1.06"D

## 4" Pedestal Monitor Mount (VOSMDMMT)

- Universal four-hole mounting pattern for use with AOM713 observation monitor
- Matte black finish

## 75-ft. Cable (CEC75)

- Can be easily daisy-chained together
- Non-corrosive locking connectors with four-pin round plug

## 25-ft. Cable (CEC25)

- Can be easily daisy-chained together
- Non-corrosive locking connectors with four-pin round plug

EXPAND your vision™