

Voyager  
**TOUGHCAM™**

# VOS7MDCL1B One-Camera Observation System



## **7" LCD Observation Monitor (AOM713)**

- High-performance LCD panel
- Energy-efficient white LED backlighting
- Back-lit controls
- Integrated audio speaker
- NTSC and PAL video signal compatible
- Three camera (A/V) inputs
- Manual (push button) or automatic (trigger) source selection
- Auto power On (standby)
- Auto/manual day/night brightness modes
- On screen display (OSD) for AV source, picture adjustment and volume level
- OSD programmable source name and distance markers
- Non-volatile memory for picture and volume
- Anti-glare/anti-scratch protective lens
- Removable sun-visor included
- Multiple mounting options



## **High-Performance Compact Color CMOS Cameras (VCMS17B)**

- High Performance Color Optics
- Waterproof IP69K
- 12 volt DC power
- Image orientation: mirror (reversed)
- Excellent low light and bright daylight performance
- 12 IR LEDs
- Microphone
- Dimensions: 2.76"W x 1.76"H x 2.07"D



## **4" Pedestal Monitor Mount (VOSHD4MNT)**

- Universal four-hole mounting pattern for use with AOM713 observation monitor
- Matte black finish



## **75-ft. Cable (CEC75)**

- Can be easily daisy-chained together
- Non-corrosive locking connectors with four-pin round plug

## **25-ft. Cable (CEC25)**

- Can be easily daisy-chained together
- Non-corrosive locking connectors with four-pin round plug

EXPAND YOUR VISION.

Voyager  
**TOUGHCAM™**

# VOS7MDCL2B Two-Camera Observation System



## **7" LCD Observation Monitor (AOM713)**

- High-performance LCD panel
- Energy-efficient white LED backlighting
- Back-lit controls
- Integrated audio speaker
- NTSC and PAL video signal compatible
- Three camera (A/V) inputs
- Manual (push button) or automatic (trigger) source selection
- Auto power On (standby)
- Auto/manual day/night brightness modes
- On screen display (OSD) for AV source, picture adjustment and volume level
- OSD programmable source name and distance markers
- Non-volatile memory for picture and volume
- Anti-glare/anti-scratch protective lens
- Removable sun-visor included
- Multiple mounting options



## **High-Performance Compact Color CMOS Cameras (VCMS17B)**

- High Performance Color Optics
- Waterproof IP69K
- 12 volt DC power
- Image orientation: mirror (reversed)
- Excellent low light and bright daylight performance
- 12 IR LEDs
- Microphone
- Dimensions: 2.76"W x 1.76"H x 2.07"D

## **4" Pedestal Monitor Mount (VOSD4MNT)**

- Universal four-hole mounting pattern for use with AOM713 observation monitor
- Matte black finish

## **75-ft. Cable (CEC75)**

- Can be easily daisy-chained together
- Non-corrosive locking connectors with four-pin round plug

## **25-ft. Cables (CEC25)**

- Can be easily daisy-chained together
- Non-corrosive locking connectors with four-pin round plug

EXPAND YOUR VISION.