

polk

ULTRAMARINE
CERTIFIED

PA450UM

AM/FM/WB/USB/SiriusXM Ready/iPod/
iPhone Ready/Bluetooth Source Unit



- 200 watts max (50W x 4) with MOSFET Power IC
- Two-piece modular design (commander and hideaway module)
- Waterproof commander (IPX6) and module (IPX5)
- AM/FM Electronic tuner (US/Euro selectable)
- Bluetooth® (A2DP/AVRCP)
- SiriusXM Ready™ (requires SXV200B tuner)
- Full iPod®/iPhone® controls and charging (via USB)
- USB jack for connection of digital media device
- NOAA seven-channel weatherband
- Auxiliary line level audio input (RCA)
- Four-channel line level audio output (RCA, front + rear)
- Two-wire power system with non-volatile memory
- Conformal coated circuit boards
- Corrosion resistant materials/finishes (ASTMB117)
- Low battery warning

DB521 5.25" Coaxial Loudspeaker

- Peak power handling: 135W
- Continuous power handling: 45W
- Soft dome tweeter
- Dynamic Balance
- Nominal impedance: 4 ohms
- Frequency response: 60-22kHz
- Sensitivity: 93dB
- Pole plate heat sink promotes better heat dissipation
- Stamped steel basket
- ABS grilles for maximum durability
- Durable butyl rubber surround
- Stainless steel mounting hardware
- Mounting dimensions: 4.68"



We Play Dirty!

asa
ELECTRONICS™
2602 Marina Drive • Elkhart, IN 46514
www.asaelectronics.com



PA D2000.2 2-Channel Class-D Power Amplifier

- 125W x 2 @ 2 ohms; 250w x 2 @ 2 ohms; 500W x 1 @ 4 ohms (bridged)
- Total frequency response: 20Hz - 20kHz
- MOSFET switching power
- Signal-to-noise ratio: 105dBA
- Max sensitivity: 200mV - 6V dB
- Protection circuitry: thermal, DC offset, reverse polarity and short circuit
- Nickel-plated wire terminals and RCA connectors
- Stainless steel hardware
- Dimensions: 1.81"H x 8.25"W x 6.75"D

PA D4000.4 2-Channel Class-D Power Amplifier

- 125W x 4 @ 4 ohms; 200W x 4 @ 2 ohms; 400w x 2 @ 4 ohms (bridged)
- Total frequency response: 20Hz - 20kHz
- MOSFET switching power
- Signal-to-noise ratio: 105dBA
- Max sensitivity: 200mV - 6V dB
- Protection circuitry: thermal, DC offset, reverse polarity and short circuit
- Nickel-plated wire terminals and RCA connectors
- Stainless steel hardware
- Dimensions: 1.81"H x 10.94"W x 6.75"D

