

## Product Change Notice

In order to ensure our products continue to evolve as the technological market changes, ASA Electronics is updating our audio accessories as follows:

The commander for the Polk Ultramarine® UM2 audio system is being discontinued. We will be offering the UMC1 App Ready Marine Controller, paired with UM2TAB module, as a replacement. This change will take effect when current supply is exhausted.

### UM2



### UMC1 + UM2TAB



- 4.3" color TFT display
- 4 Zone volume controls (when connected to UM2DSP)
- 4V Differential audio output (UM2DSP)
- 200 watts maximum power handling (50W x 4) with MOSFET Power IC
- Two-piece modular design (commander and hideaway module)
- Waterproof commander (IPX6) and module (IPX5)
- App Ready - All main functions can be controlled by any Bluetooth-enabled device with Polk Ultramarine app
- Made for iPod®/iPhone® (via Bluetooth)
- Bluetooth streaming audio (A2DP) and controls (AVRCP)
- SiriusXM-Ready® (requires SXV300V1M tuner and subscription)
- USB 2.0 for Playback of MP3 and WMA audio files
- Seven-channel NOAA weatherband
- EQ Presets
- 18 FM/12 AM/18 SAT station presets
- Auxiliary line-level audio input (RCA)
- Four-channel line-level audio output (RCA, front + rear)
- Two-wire power system with non-volatile memory
- Remote control ready (PRC100BC, PRC200BC)
- Conformal coated circuit boards
- Corrosion resistant materials/finishes (ASTM D1141)
- UV resistant materials/finishes (ASTM D4329)
- Dimensions - Module: 7.4" W x 7.4" H x 2.2" D  
Commander: 6.4" W x 4.9" H x 2.8" D

- 2.8" color TFT display viewable in direct sunlight
- Glass lens to protect display from cleaning products
- 4 Zone volume controls (when connected to UM2DSP)
- 4V Differential audio output (UM2DSP)
- 200 watts maximum power handling (50W x 4) with MOSFET Power IC
- Two-piece modular design
- IPX5 waterproof design
- App Ready - All main functions can be controlled by any Bluetooth-enabled device with Polk Ultramarine app
- Bluetooth streaming audio (A2DP) and controls (AVRCP)
- USB 2.0 for Playback of MP3 and WMA audio files
- Satellite radio compatible with satellite tuner and subscription
- Low-profile flush-mount design and detachable trim ring for front mounting
- Rotary encoder for volume control and menu-driven user interface
- EQ Presets
- 18 FM/12 AM/18 SAT station presets
- Auxiliary line-level audio input (RCA)
- Four-channel line-level audio output (RCA, front + rear)
- Two-wire power system with non-volatile memory
- Remote control ready (PRC100BC, PRC200BC)
- Conformal coated circuit boards
- Corrosion resistant (ASTM D1141)
- UV resistant (ASTM D4329)
- Dimensions: Module: 7.4" W x 7.4 H x 2.2" D  
Commander: 5.4" W x 3.75" H x 1.7" D

If you have any questions regarding this product change or want information on specific pricing, please contact your ASA sales representative or ASA Customer Service at 574-264-3135 or 800-688-3135.

Notification Date: